



PIPE TO MANHOLE SEAL
STAR-SEAL™ GASKET PER
ASTM RUBBER GASKET
SPECS C923, JOINT ALLOWS
20° OMNIDIRECTIONAL
DEFLECTION

STAR-SEAL™ GASKET
TO BE USED FOR
4" UP TO 16" PIPE.
BOOT GASKET TO
BE USED FOR
PIPE > 16".

SPECIFICATIONS:

PVC LINING AVAILABLE IF REQUIRED.

MEETS PENNDOT PUBLICATION 408.

MINIMUM CONCRETE STRENGTH 4000 PSI @ 28 DAYS

STEEL REINFORCEMENT ASTM A185 HORIZONTAL & VERTICAL STEEL

1 1/2" MIN. CONCRETE COVER (ALL REINFORCEMENT)

MANHOLE DESIGN SPEC. CONFORM TO "PRECAST REINFORCEMENT MANHOLE SECTIONS" ASTM C478, LATEST REVISION.



**Continental
Concrete
Products, Inc.**

1 South Grosstown Rd.
Pottstown, PA 19464

Phone: (610) 327-3700

Fax: (610) 327-9488

96" DIA. SANITARY SEWER MANHOLE w/STAR-SEAL™ PIPE TO MANHOLE GASKET

SIGNATURE OF APPROVAL

DATE

AR

DWG

2/08/16

72SMH

STRUCTURE